

SIP-T57W

Prime Business Phone to Deliver Optimum Desktop Productivity

Especially designed for busy executives and professionals, Yealink SIP-T57W is an easy-to-use Prime Business Phone with an adjustable 7-inch multi-point touch screen that you can not only easily and flexibly find the comfortable viewing angle according to the personal and environmental needs, but also get a rich visual presentation and easy navigation with just one-touch. With the built-in Bluetooth 4.2 and the built-in dual band 2.4G/5G Wi-Fi, the SIP T57W IP Phone ensures you to keep up with the modern wireless technology and take the first chance in the future wireless age. Its built-in USB 2.0 port allows for USB recording or a direct wired/wireless USB headset or up to three Yealink EXP50 expansion modules connection. Benefitting from these features, the Yealink SIP-T57W is a powerful and expandable office phone that delivers optimum desktop efficient and productivity.



















Wi-Fi



Multitouch Screen

Adjustable Corded-Cordless Screen

Content

USB 20

HD Audio

Built-in Bluetooth

Key Features and Benefits

- · 7" 800 x 480 capacitive adjustable touch screen
- · Adjustable LCD screen
- · Dual firmware images
- · T53/T53W/T54W/T57W firmware unified
- · Built-in Bluetooth 4.2
- · Built-in dual band 2.4G/5G Wi-Fi (802.11a/b/g/n)
- USB 2.0 port for USB recording, wired/wireless USB headsets and EXP50
- · Up to 16 VoIP accounts
- · Dual-port Gigabit Ethernet
- · PoE support
- · HAC Handset
- · Paperless label design
- · Wall mountable

Outstanding User Experience

Yealink SIP-T57W IP Phone features an adjustable 7-inch capacitive touch screen that you can readily adjust it to the comfortable viewing angle according to yourself. In addition, clearly defined set of menus is easy to navigate through when all you have to do is touching the desired option, that ensuring you an optimized interface for a



smartphone-like user experience.

HD Audio

The SIP-T57W is coupled with the latest version of Yealink Optimal HD Voice technologies, including Yealink Acoustic Shield technology, that effectively eliminate background distractions and noises, deliver crystal clear voice even in a noisy environment. Meanwhile, complying with the latest Hearing Aid Compatibility (HAC) Regulations, its HAC handset helps the person who is with hearing loss to hear the voice more clearly.

Wireless Transmission

Yealink SIP-T57W IP Phone not only furnish you with the built-in Bluetooth 4.2 for Bluetooth headsets and mobile contacts synchronization, but also the built-in dual band Wi-Fi for Wi-Fi connectivity, allowing you to access the 5G Wi-Fi connectivity handily. Also if you want to expand your horizons for busy environments, or, share one phone system with your small team by adding multiple handsets, just simply turn your IP phone to the corded-cordless phone via DECT technology. Moreover, the IP phone can function with Yealink VC Desktop together to share content from your laptop, making collaboration much easier than before.

High Expandability

A built-in USB 2.0 port allows you to enjoy USB call recording via USB flash drive. Via this USB port, you also can connect wired/wireless USB headset without connecting Yealink EHS36 anymore, and connect up to 3 Yealink expansion modules EXP50 which can be programmed with up to 180 paperless DSS keys.

Efficient Installation and Provisioning

The Yealink SIP-T57W supports efficient provisioning and effortless mass deployment with Yealink's Redirection and Provisioning Service (RPS) and Boot mechanism to help you realize the Zero Touch Provisioning without any complex manual settings. Furthermore, a unified firmware and auto-p template that applies to T53/T53W/T54W/T57W phone models, saves even more time and costs for businesses, as well as simplifies the management and maintenance.

Specifications

Specifications	Description
Audio Features	 HD voice: HD handset, HD speaker Hearing aid compatible (HAC) handset Acoustic Shield Smart Noise Filtering Audio codec: G.722, PCMU (G.711A), PCMA(G.711μ), G.729, G.729A, G.729B, G.729AB, G.726, G.723.1, iLBC DTMF: In-band, Out-of-band (RFC 2833) and SIP INFO Full-duplex hands-free speakerphone with AEC VAD, CNG, AEC, PLC, AJB, AGC



	 16 VoIP accounts One-touch speed dial, hotline
	· Call forward, call waiting, call transfer
	Mute, DND, call hold, redial, call return, auto answer
	· Group listening, SMS, emergency call
	· 10-way conferencing
	Direct IP call without SIP proxy
	· Ring tone selection/import/delete
	· Set date time manually or automatically
	· Dial plan, XML Browser, Action URL/URI
	· RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)
	· Built-in dual band Wi-Fi:
	- Network standard: IEEE802.11a/b/g/n
	- Transmission rate: Up to 433Mbps (dynamic)
	- Frequency range: 2.4GHz/5.0GHz
	· Built-in Bluetooth for:
Phone Features	- Bluetooth headset,
	- Mobile contacts synchronization
	- Bluetooth call
	- Simultaneous connection of one headset and one mobile phone
	· USB port (2.0 compliant) for:
	- Wired/wireless USB headset
	- USB call recording through USB flash drive
	- Color-screen expansion modules EXP50 (up to 3)
	- Wireless Headset Adapter EHS40
	· USB/Bluetooth connectivity to Yealink CP900/CP700 speakerphone, USB
	connectivity to Yealink UH36 headset:
	- Basic functions: Answer / end, call mute
	- Enhanced function: audio optimization, redial, call hold, volume
	synchronization, multiple calls control
	· Content Sharing (via Yealink VCD)
	· Enhanced DSS key
	· Local phonebook up to 1000 entries
	· Black list
	· XML/LDAP remote phonebook
Directory	· Smart dialing
	· Phonebook search/import/export
	· Call history: dialed/received/missed/forwarded
	. Up to 4 DECT cordiags handsots
Corded-Cordless Phone (via	 Up to 4 DECT cordless handsets Up to 4 concurrent calls
DECT Dongle DD10K)	Support Yealink W52H/W53H/W56H/DD Phone/CP930W
PECT DOUBLE DOTOK)	Slave Handset for Master Deskset
	Stave Halluset for Iviaster Desaset



IP-PBX Features	 Busy Lamp Field (BLF), Bridged Line Apperance (BLA) Anonymous call, anonymous call rejection Hot-desking, voice mail Flexible seating, Executive and Assistant Call park, call pickup Centralized call recording, call recording
Display and Indicator	 7" 800 x 480 capacitive adjustable touch screen LED for call and message waiting indication Dual-color (red or green) illuminated LEDs for line status information Wallpaper Intuitive user interface with icons and soft keys Multilingual user interface Caller ID with name, number and photo Screensaver Power saving
Feature keys	 29 one-touch DSS keys 7 feature keys: hold, transfer, message, headset, mute, redial, speakerphone Volume control keys Illuminated mute/headset/hands-free speakerphone key
Interface	 Dual-port Gigabit Ethernet Power over Ethernet (IEEE 802.3af) 1 x USB port (2.0 compliant) 1 x RJ9 (4P4C) handset port 1 x RJ9 (4P4C) headset port
Management	 Configuration: browser/phone/auto-provision Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy Auto-provision with PnP Broadsoft device management Zero-sp-touch, TR-069 Phone lock for personal privacy protection Reset to factory, reboot Package tracing export, system log



Network and Security	 SIP v1 (RFC2543), v2 (RFC3261) Call server redundancy supported NAT traversal: STUN mode Proxy mode and peer-to-peer SIP link mode IP assignment: static/DHCP HTTP/HTTPS web server Time and date synchronization using SNTP UDP/TCP/DNS-SRV(RFC 3263) QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP SRTP for voice Transport Layer Security (TLS 1.3) HTTPS certificate manager AES encryption for configuration file (AES256) Digest authentication using MD5/MD5-sess OpenVPN, IEEE802.1X, L2TP VPN IPv6, LLDP/CDP/DHCP VLAN, ICE WPA2/WPA3 Secure boot GARP (Generic Attribute Registration Protocol)
Other Physical Features	 Color: Classic Grey Wall mountable (optional) External Yealink AC adapter (optional): AC 100~240V input and DC 5V/2A output USB output currency: 5V 500mA Power consumption (PSU): 3.2W-6.3W Power consumption (PoE): 4.0W-7.8W Dimension (W*D*H*T): 259.4mm*220mm*211mm*44.5mm Operating humidity: 10~95% Operating temperature: -10~50°C (+14~122°F)
Package Features	 Package content: Yealink SIP-T57W IP phone Handset with handset cord Ethernet Cable Stand Quick Start Guide Power Adapter (Optional) Qty/CTN: 5 PCS N.W/CTN: 8.86 kg G.W/CTN: 9.79 kg Giftbox size: 324 mm*293 mm*128 mm Carton Meas: 680 mm* 303 mm*342 mm
Compliance	CE & FC HAC REACH ISO 9001 Stroadsoft 3CX. metaswitch